

Theodolite



- **Field of View** : 1°30'
- **Magnification** : 26,5x
- **Accuracy** : 2"
- **Dust/Water Rating** : IP54
- **Display** : GLCD Dual Backlit.
- **Tilt Angle Compensation** : Vertical Tilt Sensor

AXIS XT2



- **Field of View** : 1°30'
- **Magnification** : 30x
- **Accuracy** : 2"
- **Dust/Water Rating** : IP54
- **Display** : Four-Lined LCD Display
- **Tilt Angle Compensation** : Single-Axis Automatic Compensator
- **Power Supply** : Li-on 2000mAh

AXIS XT2R



Nikon

- **Field of View** : 1°20'
- **Magnification** : 30x
- **Accuracy** : 10"
- **Dust/Water Rating** : IP54
- **Display** : Backlit LCD Display.
- **Tilt Angle Compensation** : Vertical Tilt Sensor
- **Power Supply** : Baterai AA Standar (R6P/SUM-3) x 6

NIKON NE100



Nikon

- **Field of View** : 1°20'
- **Magnification** : 30x
- **Accuracy** : 7"
- **Dust/Water Rating** : IP54
- **Display** : Backlit LCD Display.
- **Tilt Angle Compensation** : Vertical Tilt Sensor
- **Power Supply** : Baterai AA Standar (R6P/SUM-3) x 6

NIKON NE101



Nikon

- **Field of View** : 1°20'
- **Magnification** : 30x
- **Accuracy** : 5"
- **Dust/Water Rating** : IP56
- **Display** : Backlit LCD Display.
- **Tilt Angle Compensation** : Vertical Tilt Sensor
- **Power Supply** : Baterai AA Standar (R6P/SUM-3) x 6

NIKON NE103



RUIDE

- **Field of View** : 1°20'
- **Magnification** : 30x
- **Accuracy** : 2"
- **Dust/Water Rating** : IP54
- **Resolving Power** : 3"
- **Display** : GLCD (160 x 96 dot)
- **Tilt Angle Compensation** : Vertical Tilt Sensor
- **Power Supply** : Rechargeable Li-on

RUIDE DISTEO 23

RUIDE

- **Field of View :** 1°30'
- **Magnification :** 30x
- **Accuracy :** 2"
- **Dust/Water Rating :** IP54
- **Display :** Four-Lined LCD Display
- **Tilt Angle Compensation :** Single-Axis Automatic Compensator
- **Power Supply :** Li-ion 2000mAh

RUIDE NT23**RUIDE**

- **Field of View :** 1°30'
- **Magnification :** 28x
- **Accuracy :** 2"
- **Dust/Water Rating :** IP54
- **Display :** Dual-face LCD Display
- **Tilt Angle Compensation :** Single-Axis Automatic Compensator
- **Power Supply :** Rechargeable Ni-H AA-sized Batteries

RUIDE RT2**SOUTH**

- **Field of View :** 1°30'
- **Magnification :** 30x
- **Accuracy :** 2"
- **Dust/Water Rating :** IP54
- **Display :** Dual-face LCD Display
- **Tilt Angle Compensation :** Single-Axis Automatic Compensator
- **Power Supply :** Rechargeable Ni-H AA-sized Batteries

SOUTH ET-02**TOPCON**

- **Field of View :** 1°30'
- **Magnification :** 30x
- **Accuracy :** 5"
- **Dust/Water Rating :** IP66
- **Display :** Dual-face LCD Display
- **Interface :** Port serial RS-232C
- **Tilt Angle Compensation :** Single-Axis Automatic Compensator
- **Power Supply :** 4 AA-Sized Batteries

TOPCON DT305L**TOPCON**

- **Field of View :** 1°30'
- **Magnification :** 30x
- **Accuracy :** 5"
- **Dust/Water Rating :** IP66
- **Display :** Dual-face LCD Display
- **Interface :** Port serial RS-232C
- **Tilt Angle Compensation :** Single-Axis Automatic Compensator
- **Power Supply :** 4 AA-Sized Batteries, Rechargeable Li-on

TOPCON DT309